Petrolimex Petrochemical Corporation - JSC
Add: 18&19th Fls, 229 Tay Son Str, Kim Lien Ward Hanoi

PRODUCT INFORMATION

CATER CF-4

Turbocharged gasoline and diesel engine oils

DECRIPTION:

CATER CF-4 is a multi-grade lubricant for turbo-charged diesel engines, formulated from high viscosity index base oils with anti-sludge, anti-wear, anti-corrosion, anti-oxidation, anti-foam additives, etc., manufactured with modern technology to protect engines operating under hard conditions in trucks, buses, light commercial vehicles, fishing boats, construction equipment and agricultural machinery.

MAIN BENEFITS:

- Good cleaning, anti-carbonation and engine protection properties
- Effectively controls piston deposit formation under high temperature engine conditions and using high sulfur fuel.
- Durable protective oil film, maximum wear protection.
- Good lubricity.

APPLICATION:

CATER CF-4 is used for high-speed turbocharged diesel engines operating under severe conditions, requiring low piston deposits.

CATER CF-4 meets SAE viscosity grade: 15W-40 and API quality grade: CF-4 for diesel engines and SG for gasoline engines.

CHARACTERISTICS:

CHARACTERISTIC	METHOD	CATER CF-4
1. Visual	-	Bright & Clear
2. Viscosity at 100°C, cSt	ASTM D445	12.5 ÷ 16.2
3. Viscosity index	ASTM D2270	Min 110
4. Flash point, °C	ASTM D92	Min 210
5. Pour point, °C	ASTM D97	-30
6. Total base number, mg KOH/g	ASTM D2896	Min 7.0

The above are typical figures generally accepted in production but are not fixed.

PACKAGES: 209L drum, 18L & 25L pail, 18L bucket.

STORAGE:

- Store in covered warehouses to prevent water intrusion and preserve labeling.
- Do not store in temperatures above 60°C or in direct sunlight or extreme cold.

HANDLING, HEALTH, AND SAFETY:

- This product is without significant risks to health and safety; however, it needs handling and uses carefully with good hygiene standards and avoids prolonged contact with skin.
- Avoid frequent contact with the eyes.
- Keep off the spark and flammable substances.
- PLC or its subsidiaries will not accept liability if the product is used other than in the manner, with precautions, or for the purpose specified.

For more details information, kindly contact PLC heads office.